

delta micro LTE delta micro plus delta micro HD

The universal film scanning systems.



The future of the past.

ZEUTSCHEL




Designed as an uncomplicated device for public or professional use, the *delta* microform scanner simply and efficiently digitizes all formats of microfilm as well as photographic materials.

Product advantages

- On-demand multiformat scanning – roll film 16/35 mm, microfiche, jackets, aperture cards and photographic slides/negatives
- now also available with color mode and high speed USB 3.0
- High-resolution area array with real-time on-screen view for highest productivity
- High-end customized lens for best microform clarity
- Follow-me-solutions
- Easy to use – touch screen, film transport motorized and fully automatic with automatic image detection
- Direct output to searchable text (OCR)
- Whisper-quiet operation – ideally for library applications

	delta micro LTE	delta micro plus	delta micro HD
Compatible film types	Microfiche; jackets; jumbo fiche; ultrafiche; microcards; 16/35 mm roll microfilm; cartridge (M-type, C-clip); aperture cards; photographic slides; negatives; 35 mm perforated films		
Image sensor	10 MP high-resolution area array with real-time on-screen view		18 MP ultra-high resolution area array with real-time on-screen view
Lens Optics	Production-level, high-end customized lens developed specifically for microform clarity		
Capture mode	Grayscale or bi-tonal	Grayscale or bi-tonal, color	
Capture time	1/3 second per image		
Reduction ratio	7x to 60x	7x to 105x	
Max. scan area	35 x 47 mm / 1.38 x 1.85 inches (on film)		
Output resolution	100-600 dpi		
Output options	Scan to file, network, USB, print, email, Cloud, Google Docs	Scan to CD/DVD, file, network, USB, print, email, Cloud, Google Docs	
Focus adjustment	Automatic and manual		
Sensor optimization	Included; fully adjustable optical image rotation		
Zoom adjustment	Motorized (optical) and digital		
File formats	TIFF (raw, compressed, single or multi); PDF (single, multi-page); JPEG; JPEG 2000; BMP; GIF; PNG		
Integrated USB output	Two built-in USB 3.0 ports / flash-drive ports (with backward compatibility)		
Scanner standards	Touch-screen; manual and motorized roll film pods, smart edit	Touch-screen; manual and motorized roll film pods; smart edit; opaque microcard LED; 3M adapter; RapidScan Batch Scanning	
Scanner options	RapidScan Batch Scanning; OCR and Annotation, Vendor interface kit, 3M adapter, Opaque microcard LED	Vendor interface kit; OCR and Annotation	
Light source	Custom-calibrated, color-compatible LED array		
Security	Integrated Kensington lock slot		
Interface	USB 3.0		
Operating system	Windows 7 Professional (64 bit only); Windows 8 (64 bit only) Intel Processor; Windows 10 (64 bit only)		
Dimensions	(w x d x h) 450 x 515 x 230 mm / 17.7 x 20.3 x 9.1 inches		
Work space	(w x d) 305 x 515 mm / 12 x 20.3 inches		
Weight	7.2 kg / 16 lbs		

We reserve the right to make technical changes without notice.



Zeitschel GmbH · Heerweg 2 · 72070 Tübingen
Tel.: +49 7071 9706-0 · Fax: +49 7071 9706-44
info@zeitschel.de · www.zeitschel.com

The future of the past.